



PRESSLABEL machine

PRESSLABEL

MACHINE FOR TRANSFER PRINTING RIBBONS AND TAPES

Automatic machine ideal for **ironing, heat-setting, transfer printing and also laminating ribbons with heat-adhesive film or heat-adhesive non-woven backing**. The ironing of the ribbons remarkably improves the aspect and the surface of the ribbons, so increasing the productivity in successive processes with label cutting and folding machines. The feeding of the woven ribbons is by a conveyor belt that keeps the length unchanged. **The ironing plate of 200 mm x 1200 mm is equipped with an automatic raising device when the machine stops**. Speed up to 100 meters per minute.


PROCESSES



RIBBON HEAT-SETTING AND IRONING



RIBBON LAMINATING



TRANSFER PRINTING ("PT" OPTION)



RIBBON REWINDING AND MEASURING

MACHINE DESCRIPTION

Two ribbon holders at in-feed.

Photocell to stop the machine at the end of the ribbon.

Ironing plate of 200 x 1200 mm with automatic raising device when the machine stops.

Safety switch protection device.

Metre counter.

Two rewinders at out-feed.

ACCESSORIES (OPTIONS)

PT

OPTION FOR TRANSFER PRINTING

Protection-paper roll holder and waste-paper rewriter is ideal for protecting the belt of the ironing surface from ink stains during transfer printing.

IP


LONGITUDINAL FOLDER

Longitudinal folder for end fold, centre fold and Manhattan fold, workable dimensions.

LONGITUDINAL END FOLD (mm)



LONGITUDINAL MANHATTAN FOLD (mm)



LONGITUDINAL CENTRE FOLD (mm)



This accessory joins the end of one ribbon to the start of another giving extremely resistant joins.

TECHNICAL DATA

OUTPUT DETAILS

IRONING PLATE MEASUREMENTS	200 x 1200 mm
RIBBON MAX WIDTH	MIN 3 mm - MAX 200 mm
MAXIMUM SPEED	Ironing with 2 ribbons: 100 m/min Transfer printing: 4 m/min Ribbon laminating: 8-14 m/min

MACHINE DETAILS

ELECTRICS	220/240 V 50/60 Hz
MAX ABSORBED POWER	7,5 kW/h
WEIGHT	430 kg
DIMENSIONS	250 x 80 x 80 h cm